

Declaration of performance

Nr. SH - 7102 - 07 - BSH

1. Unique identification code of the product type:

Glued laminated timber out of spruce

2. Intended use of the construction product according to the harmonized technical specification:

Buildings an bridges

3. Name, registered trade name or brand as well as the address of the manufacturer:

SchwörerHaus KG Hans Schwörer Straße 8 72531 Hohenstein/ Oberstetten Germany

4. Authorised representative:

No external authorised representative

5. System for the evaluation and verification of the constancy of performance:

System 1

6. Harmonized norm:

EN 14080:2013

7. Notified body:

n° 0797 Wood reserach Munich

8. Declared Performance:

Essential characteristics:	Performance
Mechanical characteristics	
Properties of wood	Wood sorted by strength according to EN 14081-1
Flexural strength	Classification based on the lamella properties according to EN 338, assignment of the strength class according to table 4 or 5, EN 14080
Compression strength	
Tensile strength	
Shear strength	Glulam made of spruce, in the strength classes GL 24h, GL 24c, GL 28h, GL 28c, GL 30h and GL 30c
Modulus of elasticity	
Adhesive strength	
Strength of finger-joints	

Fire restistance	
Geometrical data	width: 60 to 260 mm; height: 60 to 1400 mm
Adhesive strength	
Finger-joints	GL 24h, GL 24c, GL 28h, GL 28c, GL 30h and GL 30c
Bonding joint integrity of the surface bonding	Delamination test according to EN 14080, Annex C, Procedure B
Fire behaviour	D-s2, d0 according the Annex to the assigned Regulation (EU)2017/1227 the commission of 20.03.2017
Formaldehyde emission class	E1
Release of other hazardous substances	No performance specified (NPD)
Durability of adhesive stregth	
Species	Picea abies / Fichte, Abies alba / Tanne
Adhesives for finger-joints	MU, EN 301 Typ I 90 FJ 0,1S
Adhesives for surface bonding	MU, EN 301 Typ I 90 FJ 0,1S
Durability against attack by biological organisms	
Lamellas without protective treatment	Durability class against wood-destroying fungi according to EN 350:2016 for all types of products DC 5
Lamellas with protective treatment	No performance specified (NPD)

The performance of the above-mentioned product corresponds to the declared performance features. The aforesaid manufacturer is solely responsible for this declaration of performance in accordance with the regulation (EU) n° 305/2011.

Signed on behalf of the manufacturer:

Technical director, Rainer Henniger Hohenstein-Oberstetten, 22.09.2020

(Unterschrift)